

Nexion interprets Marble

APUANE COLLECTION

Apuane collection brings the flavor of the prestigious marbles extracted in the Apuan Alps (Alpi Apuane in Italian), site of the most important Italian marble quarries since the Roman times. Prestigious and rich materials that have marked architecture over the centuries.

Nexion selected four of the finest marbles to create deep and transparent surfaces, with the elegance of black and white, as well the warmth of beige and brown. Mastering polishing technique, Nexion has given to Apuane the beauty of the contemporary lappato matt alongside the evergreen full lappato surface.

The result is an elegant collection that belongs to the most recent trend of contemporary design and architecture. A collection that brings the best of the inspiring Italian design to any type of ambience and location.

Nexion about

Nexion is a brand of Nexion International, a multinational ceramic company that is the result of a partnership between two large family groups that have always been leaders in their reference markets: Ceramiche Speranza, the best in its class Italian firm founded in 1961, that has setup the state of the art manufacturing facilities in India together with the Aghara family, one of the leading players in ceramics and sanitary ware in India since 1977.

With mastery of technology and design, we turn the best of the Italian tradition and lifestyle into contemporary ceramic surfaces that can be source of inspiration for architects and designers around the world.

Open-minded and keen to learn from customers and partners, we are committed to deliver the best quality and service and we believe that our work ends when our clients fulfill their desires and achieve their goals.

Headquarters & Indian Sales
Nexion International Private Limited
1104, Shapath V, S.G. Road
Ahmedabad, Gujarat (India)
indians@nexiontiles.com
www.nexiontiles.com

Design, Marketing & Global Sales
Via 2 Giugno, 13
41042 Fiorano Modenese
Modena (Italy)
globalcs@nexiontiles.com
www.nexiontiles.com

MARBLE | Apuane



Full body-colored porcelain stoneware (International standard) | Vitrified stoneware (Indian standard)
Rectified | 9 mm thickness

4 Inspirations
varieties of marble in different elegant and suggestive tones.



Statuario 80x160 cm
F86APLAOYRO Lappato Matt
F86APLAOLRO Full Lappato



Botticino 80x160 cm
F86APLBOYRO Lappato Matt
F86APLBOLRO Full Lappato



Corinthian Beige 80x160 cm
F86APLBIYRO Lappato Matt
F86APLBILRO Full Lappato



Antique Black 80x160 cm
F86APLKOYRO Lappato Matt
F86APLKOLRO Full Lappato

4 Sizes
to exploit all architectural and creative potential.


120x240 cm | 80x160 cm
120x120 cm | 60x120 cm



Statuario 120x240 cm
F14APNAOYRO Lappato Matt
F14APNAOLRO Full Lappato



Botticino 120x240 cm
F14APNBOYRO Lappato Matt
F14APNBOLRO Full Lappato



Corinthian Beige 120x240 cm
F14APNBIYRO Lappato Matt
F14APNBILRO Full Lappato



Antique Black 120x240 cm
F14APNKOYRO Lappato Matt
F14APNKOLRO Full Lappato



Statuario 120x120 cm
F12APNAOYRO Lappato Matt
F12APNAOLRO Full Lappato




Botticino 120x120 cm
F12APNBOYRO Lappato Matt
F12APNBOLRO Full Lappato



Corinthian Beige 120x120 cm
F12APNBIYRO Lappato Matt
F12APNBILRO Full Lappato



Antique Black 120x120 cm
F12APNKOYRO Lappato Matt
F12APNKOLRO Full Lappato




Statuario 60x120 cm
F62APNAOYRO Lappato Matt
F62APNAOLRO Full Lappato



Botticino 60x120 cm
F62APNBOYRO Lappato Matt
F62APNBOLRO Full Lappato



Corinthian Beige 60x120 cm
F62APNBIYRO Lappato Matt
F62APNBILRO Full Lappato



Antique Black 60x120 cm
F62APNKOYRO Lappato Matt
F62APNKOLRO Full Lappato

Nexion installation suggestions

Nexion recommends 2 mm joint for optimal aesthetics taking advantage of the tiles caliber in multi-sized applications. Both cement and epoxy grout can be used; grout-design color matching advisable for optimal aesthetics. It is not recommended to use grouting with colored pigments in contrast with the color of the tiles. For detailed installation guidelines log on www.nexiontiles.com

Nexion quality standards

ALL TESTS ARE CARRIED OUT BY ITALIAN LABORATORIES ACCREDITED ACCORDING TO ISO/IEC 17025:2017
Standards according to ISO 13006: Annex G - EN 14411: Annex G. Dry - Pressed Ceramic Tiles.

QUALITY ITEMS	TECHNICAL FEATURE	STANDARD METHOD ISO	UNIT	REQUIREMENTS ISO 13006:2018(E) E _v < 0,5% GROUP B1a	NEXION Values			
					SIZE < 1200 mm		SIZE ≥ 1200 mm (SLABS)	
					%	mm	%	mm
DIMENSIONS AND SURFACE QUALITY	Width	ISO 10545 - 2	mm	+ 0.3%	± 0.1%	± 0.8 mm	± 0.1%	± 1 mm
	Length	ISO 10545 - 2	mm	+ 0.3%	± 0.1%	± 0.8 mm	± 0.1%	± 1.2 mm
	Thickness	ISO 10545 - 2	mm	+ 5.0%	± 4%	± 0.5 mm	± 4%	± 0.5 mm
	Straightness of Side	ISO 10545 - 2	mm	+ 0.3%	± 0.1%	± 0.8 mm	± 0.1%	± 1 mm
	Rectangularity	ISO 10545 - 2	mm	+ 0.3%	± 0.1%	+ 1.3 mm	± 0.1%	+ 1.5 mm
	Surface Flatness	ISO 10545 - 2	mm	+ 0.4%	± 0.1%	+ 1.8 mm	± 0.2%	+ 3 mm
	Surface Quality	ISO 10545 - 2	-	A minimum of 95% of the tiles are to be free from visible defects which can impair the appearance of a major area of tiles	95%			
PHYSICAL PROPERTIES	Water Absorption	ISO 10545 - 3	%	< 0.5% Individual 0,6%	Avg. < 0,08% Individual 0,2%			
	Modulus of Rupture	ISO 10545 - 4	N/mm ²	Min. 35, Individual Min. 32	Min. 42			
	Breaking Strength	ISO 10545 - 4	N	Not less than 1300	Min. 1800			
	Moisture Expansion	ISO 10545 - 10	mm/m	-	0,02			
	Surface Abrasion	ISO 10545-7	Class	Minimum Class-II Report abrasion class and cycles passed	Class III			
	Resistance to surface abrasion of glazed tiles intended for use on floors							
	Mohs Hardness of surface	NA	-	-	4			
	Coefficient of linear thermal expansion from ambient temperature to 100 °C	ISO 10545 - 8	K ¹	As declared by the Manufacturer	6x10 ⁻⁶ K ⁻¹ max			
	Thermal Shock Resistance	ISO 10545 - 9	-	As declared by the Manufacturer	No damage			
	Crazing Resistance: glazed tiles	ISO 10545 - 11	-	Required	No damage for Min. 10 Cycles			
Bulk Density	ISO 10545 - 3	g/cc	2,2	2,2				
Impact Resistance	ISO 10545 - 5	-	As declared by the Manufacturer	0,55				
Frost Resistance	ISO 10545 - 12	-	As declared by the Manufacturer	No change				
CHEMICAL PROPERTIES	Small color differences	ISO 10545 - 16	-	Plain colored tiles only where required UGL: AE < 0,75	No change			
	Resistance to staining	ISO 10545 - 14	Class	Minimum Class 3	Class 4			
	Resistance to household chemicals and swimming pool salts	ISO 10545 - 13	Class	Minimum B	Minimum A			
	Resistance to acids & alkalis	ISO 10545 - 13	Class	As declared by the Manufacturer	Minimum B			

Packaging info

Shipments to domestic markets (India)

Nominal Size cm	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)
120x240	9	1	2,87	61,00
80x160	9	2	2,55	54,00
120x120	9	2	2,87	60,00
60x120	9	2	1,43	30,00

Worldwide shipments

Nominal Size cm	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)	Box x pallet	Sq. mt x pallet	Pallet weight (Kg)
120x240	9	1	2,87	61,00	37	106,30	2347,00
80x160	9	2	2,55	54,00	28	71,40	1582,00
120x120	9	2	2,87	60,00	24	68,88	1510,00
60x120	9	2	1,43	30,00	32	45,82	1003,00

Tiles are packaged in a random manner and company cannot guarantee the type of faces inside each package.

