

Nexion interprets Marble

POMPEII COLLECTION

Pompeii collection conveys the richness of some of the precious marbles used since the Roman age to place the milestones along the most important ways of communication and elevates the status of prestigious patrician villas and mansions.

Nexion selected four among the finest marbles and created slabs in eye-catching color variations ranging from the classical beauty of white Italian lasa to the richness of beige Iranian onyx, to intense tones of grigio pulpis and grigio emperador. With great craftsmanship, Nexion has exalted these stones with two captivating surfaces: the contemporary lappato matt and the super-reflective full lappato.

The result is a collection that translates the timeless charm of some of the most precious marbles in a contemporary language, ideal for the most ambitious design projects. A collection that brings the best of the inspiring Italian design to any type of ambience and location.

Nexion about

Nexion is a brand of Nexion International, a multinational ceramic company that is the result of a partnership between two large family groups that have always been leaders in their reference markets: Ceramiche Speranza, the best in its class Italian firm founded in 1961, that has setup the state of the art manufacturing facilities in India together with the Aghara family, one of the leading players in ceramics and sanitary ware in India since 1977.

With mastery of technology and design, we turn the best of the Italian tradition and lifestyle into contemporary ceramic surfaces that can be source of inspiration for architects and designers around the world.

Open-minded and keen to learn from customers and partners, we are committed to deliver the best quality and service and we believe that our work ends when our clients fulfill their desires and achieve their goals.

Headquarters & Indian Sales
Nexion International Private Limited
1104, Shapath V, S.G. Road
Ahmedabad, Gujarat (India)
indians@nexiontiles.com
www.nexiontiles.com


Design, Marketing & Global Sales
Via 2 Giugno, 13
41042 Fiorano Modenese
Modena (Italy)
globalcs@nexiontiles.com
www.nexiontiles.com

MARBLE | Pompeii



Full body-colored porcelain stoneware (International standard) | Vitrified stoneware (Indian standard)
Rectified | 9 mm thickness

4 Inspirations
precious marbles for the most ambitious design projects.



Onice Persiano 80x160 cm
F86PMNEOYRO Lappato Matt
F86PMNEOLRO Full Lappato



Emperador Grigio 80x160 cm
F86PMNGIYRO Lappato Matt
F86PMNGILRO Full Lappato



Pulpis Grigio 80x160 cm
F86PMNGOYRO Lappato Matt
F86PMNGOLRO Full Lappato



Bianco Lasa 80x160 cm
F86PMNAOYRO Lappato Matt
F86PMNAOLRO Full Lappato

4 Sizes
to exploit all architectural and creative potential.

120x240 cm | 80x160 cm
120x120 cm | 60x120 cm



Onice Persiano 120x240 cm
F14PMPEOYRO Lappato Matt
F14PMPEOLRO Full Lappato




Emperador Grigio 120x240 cm
F14PMPGIYRO Lappato Matt
F14PMPGILRO Full Lappato



Pulpis Grigio 120x240 cm
F14PMPGOYRO Lappato Matt
F14PMPGOLRO Full Lappato



Bianco Lasa 120x240 cm
F14PMPAOYRO Lappato Matt
F14PMPAOLRO Full Lappato



Onice Persiano 120x120 cm
F12PMNEOYRO Lappato Matt
F12PMNEOLRO Full Lappato



Emperador Grigio 120x120 cm
F12PMNGIYRO Lappato Matt
F12PMNGILRO Full Lappato



Pulpis Grigio 120x120 cm
F12PMNGOYRO Lappato Matt
F12PMNGOLRO Full Lappato



Bianco Lasa 120x120 cm
F12PMNAOYRO Lappato Matt
F12PMNAOLRO Full Lappato



Onice Persiano 60x120 cm
F62PMPEOYRO Lappato Matt
F62PMPEOLRO Full Lappato



Emperador Grigio 60x120 cm
F62PMPGIYRO Lappato Matt
F62PMPGILRO Full Lappato



Pulpis Grigio 60x120 cm
F62PMPGOYRO Lappato Matt
F62PMPGOLRO Full Lappato



Bianco Lasa 60x120 cm
F62PMPAOYRO Lappato Matt
F62PMPAOLRO Full Lappato

Nexion installation suggestions

Nexion recommends 2 mm joint for optimal aesthetics taking advantage of the tiles caliber in multi-sized applications. Both cement and epoxy grout can be used; grout-design color matching advisable for optimal aesthetics. It is not recommended to use grouting with colored pigments in contrast with the color of the tiles. For detailed installation guidelines log on www.nexiontiles.com

Nexion quality standards

ALL TESTS ARE CARRIED OUT BY ITALIAN LABORATORIES ACCREDITED ACCORDING TO ISO/IEC 17025:2017
Standards according to ISO 13006: Annex G - EN 14411: Annex G, Dry - Pressed Ceramic Tiles.

QUALITY ITEMS	TECHNICAL FEATURE	STANDARD METHOD ISO	UNIT	REQUIREMENTS ISO 13006:2018(E) E _v < 0,5% GROUP B1a	NEXION Values			
					SIZE < 1200 mm		SIZE ≥ 1200 mm (SLABS)	
					%	mm	%	mm
DIMENSIONS AND SURFACE QUALITY	Width	ISO 10545 - 2	mm	+ 0,3%	± 0,1%	+ 0,8 mm	± 0,1%	± 1 mm
	Length	ISO 10545 - 2	mm	+ 0,3%	± 0,1%	+ 0,8 mm	± 0,1%	+ 1,2 mm
	Thickness	ISO 10545 - 2	mm	+ 5,0%	± 4%	+ 0,5 mm	± 4%	± 0,5 mm
	Straightness of Side	ISO 10545 - 2	mm	+ 0,3%	± 0,1%	+ 0,8 mm	± 0,1%	+ 1 mm
	Rectangularity	ISO 10545 - 2	mm	+ 0,3%	± 0,1%	+ 1,3 mm	± 0,1%	+ 1,5 mm
	Surface Flatness	ISO 10545 - 2	mm	+ 0,4%	± 0,1%	+ 1,8 mm	± 0,2%	+ 3 mm
	Surface Quality	ISO 10545 - 2	-	A minimum of 95% of the tiles are to be free from visible defects which can impair the appearance of a major area of tiles	95%			
PHYSICAL PROPERTIES	Water Absorption	ISO 10545 - 3	%	≤ 0,5% Individual 0,6%	Avg. ≤ 0,08% Individual 0,2%			
	Modulus of Rupture	ISO 10545 - 4	N/mm ²	Min. 35, Individual Min. 32	Min. 1800			
	Breaking Strength	ISO 10545 - 4	N	Not less than 1300	Min. 1800			
	Moisture Expansion	ISO 10545 - 10	mm/m	-	0,02			
	Surface Abrasion	ISO 10545-7	Class	Minimum Class -II Report abrasion class and cycles passed	Class III			
	Resistance to surface abrasion of glazed tiles intended for use on floors							
	Mohs Hardness of surface	NA	-	-	4			
	Coefficient of linear thermal expansion from ambient temperature to 100 °C	ISO 10545 - 8	K ⁻¹	As declared by the Manufacturer	6x10 ⁻⁶ K ⁻¹ max			
	Thermal Shock Resistance	ISO 10545 - 9	-	As declared by the Manufacturer	No damage			
	Crazing Resistance: glazed tiles	ISO 10545 - 11	-	Required	No damage for Min. 10 Cycles			
	Bulk Density	ISO 10545 - 3	g/cc	2,2	2,2			
	Impact Resistance	ISO 10545 - 5	-	As declared by the Manufacturer	0,55			
Frost Resistance	ISO 10545 - 12	-	As declared by the Manufacturer	No change				
Small color differences	ISO 10545 - 16	-	Plain colored tiles only where required UGL: AE < 0,75	No change				
CHEMICAL PROPERTIES	Resistance to staining	ISO 10545 - 14	Class	Minimum Class 3	Class 4			
	Resistance to household chemicals and swimming pool salts	ISO 10545 - 13	Class	Minimum B	Minimum A			
	Resistance to acids & alkalis	ISO 10545 - 13	Class	As declared by the Manufacturer	Minimum B			

Packaging info

Shipments to domestic markets (India)

Nominal Size cm	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)
120x240	9	1	2,87	61,00
80x160	9	2	2,55	54,00
120x120	9	2	2,87	60,00
60x120	9	2	1,43	30,00

Worldwide shipments

Nominal Size cm	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)	Box x pallet	Sq. mt x pallet	Pallet weight (Kg)
120x240	9	1	2,87	61,00	37	106,30	2347,00
80x160	9	2	2,55	54,00	28	71,40	1582,00
120x120	9	2	2,87	60,00	24	68,88	1510,00
60x120	9	2	1,43	30,00	32	45,82	1003,00

Tiles are packaged in a random manner and company cannot guarantee the type of faces inside each package.



