

STONE | Pietra del Cardoso



Nexion interprets Stone

PIETRA DEL CARDOSO COLLECTION

Pietra del Cardoso collection inherits the spirit of the homonymous Italian stone extracted from the mountains of Tuscany, home of most famous marble quarries in the world (Alpi Apuane). A material appreciated for centuries due to its extraordinary longevity, resistance, style and functionality.

Nexion has accurately selected some of the most exclusive specimens conveying the essence of Cardoso into a new unique ceramic material, combining elegance with unrivalled technical qualities. Nexion has bring this stone to the next level, devising an extremely durable surface, highly resistant to chemicals, stains and abrasions which makes it particularly suitable for high traffic public spaces.

The result is an extremely wide and versatile offering, divided into six colors, five sizes, three surfaces and two anti-slip finishes. A collection that bring the best inspiration of contemporary Italian design in every type of space and environment.

Nexion about

Nexion is a brand of Nexion International, a multinational ceramic company that is the result of a partnership between two large family groups that have always been leaders in their reference markets: Ceramiche Speranza, the best in its class Italian firm founded in 1961, that has setup the state of the art manufacturing facilities in India together with the Aghara family, one of the leading players in ceramics and sanitary ware in India since 1977.

With mastery of technology and design, we turn the best of the Italian tradition and lifestyle into contemporary ceramic surfaces that can be source of inspiration for architects and designers around the world.

Open-minded and keen to learn from customers and partners, we are committed to deliver the best quality and service and we believe that our work ends when our clients fulfill their desires and achieve their goals.

Headquarters & Indian Sales
Nexion International Pvt Ltd
1104, Shapath V, S.G. Road
Ahmedabad, Gujarat (India)
indians@nexiontiles.com
www.nexiontiles.com

Design, Marketing & Global Sales
Via 2 Giugno, 13
41042 Fiorano Modenese
Modena (Italy)
globals@nexiontiles.com
www.nexiontiles.com

Full body-colored porcelain stoneware (international standard) | Vitrified stoneware (indian standard).
Rectified | 9 mm thickness

6 Inspirations

varieties of marble in different elegant and suggestive tones.

1 Size

to exploit all architectural and creative potential.

60x120 cm

2 Finishes

to find the most indicate surface for every location.

R9, R11 and R12 finishes on request



Beige Chiaro 60X120 cm
F62PDCB0PRO Lappato in Cresta



Beige Chiaro 60X120 cm
F62PDCB0NRO Naturale



Beige Medio 60X120 cm
F62PDCB1PRO Lappato in Cresta



Beige Medio 60X120 cm
F62PDCB1NRO Naturale



Beige Scuro 60X120 cm
F62PDCB2PRO Lappato in Cresta



Beige Scuro 60X120 cm
F62PDCB2NRO Naturale



Grigio Chiaro 60X120 cm
F62PDCG0PRO Lappato in Cresta



Grigio Chiaro 60X120 cm
F62PDCG0NRO Naturale



Grigio Medio 60X120 cm
F62PDCG1PRO Lappato in Cresta



Grigio Medio 60X120 cm
F62PDCG1NRO Naturale



Grigio Scuro 60X120 cm
F62PDCG2PRO Lappato in Cresta



Grigio Scuro 60x120 cm
F62PDCG2NRO Naturale

Nexion installation suggestions

Nexion recommends 2 mm joint for optimal aesthetics taking advantage of the tiles caliber in multi-sized applications.

Both cement and epoxy grout can be used; grout-design color matching advisable for optimal aesthetics.

It is not recommended to use grouting with colored pigments in contrast with the color of the tiles.

For detailed installation guidelines log on www.nexiontiles.com

Nexion quality standards

ALL TESTS ARE CARRIED OUT BY ITALIAN LABORATORIES ACCREDITED ACCORDING TO ISO/IEC 17025:2017
Standards according to ISO 13006: Annex G - EN 14411: Annex G. Dry - Pressed Ceramic Tiles.

QUALITY ITEMS	TECHNICAL FEATURE	STANDARD METHOD ISO	UNIT	REQUIREMENTS ISO 13006:2018(E) Ex. 9.5% GROUP Bla	NEXION Values			
					SIZE < 1200 mm		SIZE ≥ 1200 mm (SLABS)	
					%	mm	%	mm
DIMENSIONS AND SURFACE QUALITY	Width	ISO 10545 - 2	mm	+ 0,3%	+ 0,1%	+ 0,8 mm	+ 0,1%	+ 1 mm
	Length	ISO 10545 - 2	mm	+ 0,3%	+ 0,1%	+ 0,8 mm	+ 0,1%	+ 1,2 mm
	Thickness	ISO 10545 - 2	mm	+ 5,0%	+ 4%	+ 0,5 mm	+ 4%	+ 0,5 mm
	Straightness of Side	ISO 10545 - 2	mm	+ 0,3%	+ 0,1%	+ 0,8 mm	+ 0,1%	+ 1 mm
	Rectangularity	ISO 10545 - 2	mm	+ 0,3%	+ 0,1%	+ 1,3 mm	+ 0,1%	+ 1,5 mm
	Surface Flatness	ISO 10545 - 2	mm	+ 0,4%	+ 0,1%	+ 1,8 mm	+ 0,2%	+ 3 mm
	Surface Quality	ISO 10545 - 2	-	A minimum of 95% of the tiles are to be free from visible defects which can impair the appearance of a major area of tiles	95%			
PHYSICAL PROPERTIES	Water Absorption	ISO 10545 - 3	%	≤ 0,5% Individual 0,6%	Avg. ≤ 0,08% Individual 0,2%			
	Modulus of Rupture	ISO 10545 - 4	N/mm ²	Min. 35, Individual Min. 32	Min. 42			
	Breaking Strength	ISO 10545 - 4	N	Not less than 1300	Min. 1800			
	Moisture Expansion	ISO 10545 - 10	mm/m	-	0,02			
	Surface Abrasion							
	Resistance to surface abrasion of glazed tiles intended for use on floors	ISO 10545-7	Class	Minimum Class -II Report abrasion class and cycles passed	Class IV			
	Mohs Hardness of surface	NA	-	-	7			
	Coefficient of linear thermal expansion from ambient temperature to 100 °C	ISO 10545 - 8	K ⁻¹	As declared by the Manufacturer	6x10 ⁻⁶ K ⁻¹ max			
	Thermal Shock Resistance	ISO 10545 - 9	-	As declared by the Manufacturer	No damage			
	Crazing Resistance: glazed tiles	ISO 10545 - 11	-	Required	No damage for Min. 10 cycles			
	Bulk Density	ISO 10545 - 3	g/cc	2,2	2,2			
CHEMICAL PROPERTIES	Impact Resistance	ISO 10545 - 5	-	As declared by the Manufacturer	0,55			
	Frost Resistance	ISO 10545 - 12	-	As declared by the Manufacturer	No change			
	Slip Resistance	ANSI A1371 DIN 51130	-	As declared by the Manufacturer	DCOF > 0,51 R-10			
	Small color differences	ISO 10545 - 16	-	Plain colored tiles only where required UGL ΔE < 1,0	No change			
	Resistance to staining	ISO 10545 - 14	Class	Minimum Class 3	Class 4			
Resistance to household chemicals and swimming pool salts	ISO 10545 - 13	Class	Minimum B	Minimum A				
Resistance to acids & alkalis	ISO 10545 - 13	Class	As declared by the Manufacturer	Minimum B				

Packaging info

Shipments to domestic markets (India)

Nominal	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)
60x120	9	2	1,43	30,00

Worldwide shipments

Nominal	Thickness mm	Pcs. x box	Sq. mt x box	Weight x box (Kg)	Box x pallet	Sq. Mts x pallet	Pallet weight
60x120	9	2	1,43	30,00	32,00	45,82	1003,00

Size

Nominal Size cm	Actual Size cm
60x120	59,8x119,8



